

Product Name: GLISTEN WINDOW CLEANER

Date of Issue: NOV 2016 Page 1 of Total 7

SECTION 1 – STATEMENT OF CHEMICAL PRODUCT AND COMPANY IDENTIFICATION				
Trade Name:	GLISTEN WINDOW CLEANER			
SUPPLIER:	ECOCLEAN UTILITY AGENCIE	ECOCLEAN UTILITY AGENCIES PTY LTD		
ADDRESS:	PO Box 6224 YATALA DC 420	PO Box 6224 YATALA DC 4207		
TELEPHONE:	(07) 5549 3622	FAX:	(07) 5549 3666	
EMERGENCY PHONE:	13 1126 in Australia.	ABN:	72 135 037 160	
Substance:	water based liquid	Product Use:	Window cleaner	
Creation Date:	November 2016	Revision Date:	November 2021	

SECTION 2 – HAZARDS IDENTIFICA	ATION	
Classification of the substance or	mixture	
Poisons Schedule	Not scheduled	
Dangerous Goods	Classified as Dangerous Goods class 3 Flammable	
GHS Classification	Eye Irritation Category 2A	
	Flammable Liquids Category 3	
Label elements	, ,	
GHS label pictograms	₹!>	
Signal word	WARNING	
Hazard statement(s)		
H319	Causes serious eye irritation.	
H226	Flammable liquid and vapour.	
Precautionary statement(s): General		
P102	Keep out of reach of children.	
P103	Read label before use.	
Precautionary statement(s): Prev	ention	
P264	Wash skin thoroughly after handling.	
P280	Wear protective gloves/protective clothing/eye protection/face protection.	
P210	Keep away from heat/sparks/open flames/hot surfaces. — No smoking.	
P233	Keep container tightly closed.	
P240	Ground/bond container and receiving equipment.	
P241	Use explosion-proof electrical/ventilating/lighting//equipment.	
P242	Use only non-sparking tools.	
P243	Take precautionary measures against static discharge.	
Precautionary statement(s): Resp	onse	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if	
	present and easy to do. Continue rinsing.	
P337 + P313	If eye irritation persists: Get medical advice/attention.	
P303 + P361 + P353	3 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin.	
P370 + P378	In case of fire: Use water spray, alcohol resistant foam, dry chemicals or carbon dioxide for	
	extinction.	
Precautionary statement(s): Storage		
P403 + P235	Store in a well-ventilated place. Keep cool.	



Product Name: GLISTEN WINDOW CLEANER

Date of Issue: NOV 2016 Page 2 of Total 7

Precautionary statement(s): Disposal		
P501	Dispose of contents/ container in accordance with local regulations.	
Note		
IMPORTANT This SDS and the Hazard Classifications contained therein, only apply to the product i		
	concentrated form, as supplied. When diluted to 1:5 or greater they no longer apply.	
	However, good hygiene and housekeeping practices should be adhered to.	

SECTION 3 – COMPOSITION AND INFORMATION ON INGREDIENTS			
Ingredients:	CAS Number:	Proportion:	
isopropyl alcohol	67-63-0	10 - 30% w/w	
Ethylene glycol monobutyl ether	111-76-2	< 10% w/w	
Ingredients determined to be non-			
hazardous (chelating agents, surfatants,	various	< 10 % w/w	
dye)			
Water	7732-18-5	To 100 % w/w	

NOTE: Ingredients determined not to be hazardous are present in concentrations that do not exceed the relevant cut-off concentrations as found from NOHSC publication "List of Designated Hazardous Substances" or have been found NOT to meet the criteria of a hazardous substance as defined in the NOHSC publication "Approved Criteria for Classifying Hazardous Substances", or have been found NOT to meet the criteria of a dangerous substance as defined in the GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS (GHS), 4th edition United Nations 2011. Listed ingredients may be below the cut-off concentrations for classification as hazardous, but are listed for information purposes and for additive effects.

SECTION 4 – FIRST AID I	MEASURES
Inhalation	Remove victim to fresh air away from exposure. Obtain medical attention if symptoms occur.
Skin contact	Immediately wash contaminated skin with plenty of soap and water. Remove contaminated
	clothing and wash before re-use. Seek medical advice (e.g. doctor) if irritation, burning or redness persists.
Eye contact	If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. If symptoms persist, seek medical attention.
Ingestion	Do NOT induce vomiting. Do NOT attempt to give anything by mouth to an unconscious person. Rinse mouth thoroughly with water immediately. Give water to drink. If vomiting occurs, give further water to achieve effective dilution. Seek medical advice (e.g. doctor).
Advice to Doctor	Treat symptomatically.
Scheduled Poisons	Poisons Information Centre in each Australian State capital city or in Christchurch, New Zealand can provide additional assistance for scheduled poisons. (Phone Australia 131126 or New Zealand 0800 764 766).
First Aid Facilities	Eye wash station. Normal washroom facilities.

SECTION 5 – FIRE FIGHTING MEASURES		
Fire and Explosion	Water/alcohol based. In use, may form flammable/explosive vapourair mixture. If involved in a	
Hazards	fire will emit toxic fumes.	
Extinguishing Media	Use extinguishing media appropriate to surrounding fire conditions. Use carbon dioxide (CO2)	
	fire extinguisher, water fog or alcohol resistant foam or fine water spray.	
Fire Fighting	Keep containers exposed to extreme heat cool with water spray. Fire fighters to wear self-	
	contained breathing apparatus if risk of exposure to products of combustion or decomposition.	
Flash Point	Flash point ca 29°C	



Product Name: GLISTEN WINDOW CLEANER

Date of Issue: NOV 2016 Page 3 of Total 7

Emergency Procedures

HAZCHEM code: ●3Y

•3 = use ALCOHOL RESISTANT FOAM to fight fires.

Y = Yes - risk of violent reaction, recommend full fire kit and breathing apparatus for fire only, CONTAIN.

- Shut off engine and electrical equipment off.
- No smoking or naked lights within 50 metres.
- Move people from immediate area; keep upwind.
- Send messenger to notify fire brigade and police.
- Tell them location, material quantity, UN number and emergency contact. Indicate condition of vehicle and damage or injuries observed.
- Warn other traffic.

Occupational Release

Minor spills do not normally need any special clean-up measures. In the event of a major spill, prevent spillage from entering drains or water-courses. For large spills, or tank rupture, consider initial evacuation distance of 200 metres in all directions. Stop leak if safe to do so. If available, use water spray to disperse vapour. Wear appropriate protective equipment as in section 8 below to prevent skin and eye contamination. Spilt material may result in a slip hazard and should be absorbed into dry, inert material (e.g. sand, earth or vermiculite), which then can be put into appropriately labelled drums for disposal by an approved agent according to local conditions. Residual deposits will remain slippery. Wash area down with excess water. If contamination of sewers or waterways has occurred advise the local emergency services. In the event of a large spillage notify the local environment protection authority or emergency services.

SECTION 7 – HAND	LING AND STORAGE
Handling	Avoid skin or eye contact with concentrate. Wear protective clothing when risk of exposure occurs. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers closed at all times. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered. Launder contaminated clothing before re-use.
Storage	Store in a cool, dry, well-ventilated area, out of direct sunlight. Protect from freezing. Store in suitable, labelled containers. Keep containers tightly closed. Store away from incompatible materials and ignition sources. Ensure that storage conditions comply with applicable local and national regulations.

SECTION 8 – EXPOSUR	E CONTROLS AND PERSONAL PROTECTION
Exposure Limits	National Occupational Exposure Limits, as published by National Occupational Health & Safety
	Commission:
	Time-weighted Average (TWA):
	None established for product.
	Isopropyl alcohol: 400 ppm (983 mg/m3)
	Ethylene glycol monobutyl ether: 20ppm (96.9 mg/m3)
	Short Term Exposure Limit (STEL):
	None established for product.
	Isopropyl alocohol: 500 ppm (1230 mg/m3)
	Ethylene glycol monobutyl ether: 50 ppm (242 mg/m3)
Ventilation	Ensure ventilation is adequate to maintain air concentrations below exposure standards. Avoid
	generating mists of the product. Use only in a well-ventilated area. Ensure airflow, where this
	product is used, is directed away from the operators.



Product Name: GLISTEN WINDOW CLEANER

Date of Issue: NOV 2016 Page 4 of Total 7

Personal Protective Equipment	Use good occupational work practice. The use of protective clothing and equipment depends upon the degree and nature of exposure. The following protective equipment should be available;
Eye Protection	Safety glasses with full face shield should be used for handling concentrate in quantity, cleaning up spills, decanting, etc. Eye protection devices should conform to relevant regulations. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.
Hand Protection	Generally not required for typical applications with diluted solutions as per label directions. Wear gloves of impervious material such as butyl rubber, natural latex, neoprene, PVC and nitrile – to handle in quantity, clean up spills, decanting, etc. Final choice of appropriate gloves will vary according to individual circumstances. i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.
Body Protection	Suitable protective workwear, e.g. rubber or plastic apron, sleeves, boots and cotton overalls buttoned at neck and wrist are recommended. Chemical resistant apron is recommended where large quantities are handled.
Respirator	Generally not required for typical applications with diluted solutions as per label directions. If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable vapor/mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES			
Physical State	Non-viscous liquid	Colour	Blue
Odour	characteristic odour	Specific Gravity	0.96 – 0.98 @ 25 ºC
Boiling Point	Approximately 100 °C	Freezing Point	Approximately 0 °C
Vapour Pressure	Not available	Vapour Density	Not available
Flash Point	Approximately 29 °C	Flammable Limits	Not available
Water Solubility	Miscible in all proportions	рН	4.0 – 6.0 neat
Volatile Organic Compounds (VOC)	Ca 20 % v/v	Per Cent Volatile	Ca 98 % v/v
Viscosity	Not available	Odour Threshold	Not available

SECTION 10 – STABILITY AND REACTIVITY		
Reactivity	Stable at normal temperatures and pressure.	
Conditions to Avoid	Extremes of temperature and direct sunlight.	
Incompatibilities	Reducing agents, oxidizing agents.	
Hazardous		
Decomposition	Thermal decomposition (burning) may result in the release of toxic and/or irritating fumes.	

SECTION 11 – TOXICOLOGICAL INFORMATION		
POTENTIAL HEALTH EFFECTS		
No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label.		
Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:		
Inhalation	Not considered to be an inhalation hazard.	
Skin contact	Not expected to be irritating to skin.	



Product Name: GLISTEN WINDOW CLEANER

Date of Issue: NOV 2016 Page 5 of Total 7

Eye contact	Concentrated product causes eye irritation. Eye contact with concentrate will cause stinging, blurring, tearing.
Ingestion	Ingestion of this product may irritate the gastric tract causing nausea and vomiting.
Chronic exposure	No known effects.
Toxicology Information	Not toxic, based on ingredients. Oral LD50 (calculated) : >10,000 mg/L
Carcinogen Status	
NOHSC	No significant ingredient is classified as carcinogenic by NOHSC.
NTP	No significant ingredient is classified as carcinogenic by NTP.
IARC	No significant ingredient is classified as carcinogenic by IARC.
Respiratory sensitisation	Not expected to be a respiratory sensitizer.
Skin Sensitisation	Not expected to be a skin sensitizer.
Germ cell mutagenicity	Not considered to be a mutagenic hazard.
Reproductive Toxicity	Not considered to be toxic to reproduction.
STOT-single exposure	Not expected to cause toxicity to a specific target organ.
STOT-repeated exposure	Not expected to cause toxicity to a specific target organ.
Aspiration Hazard	Not expected to be an aspiration hazard.

SECTION 12 – ECOLOGICAL	INFORMATION
Eco-toxicity	Not harmful to aquatic life. LC50 > 100mg/L.
Product (as sold)	Acute Aquatic Toxicity (Calculated) LC50: 2000 - 9000 mg/L.
	Acute Aquatic Toxicity NOT HAZARDOUS
Eco-toxicity	Not harmful to aquatic life. LC50 > 100mg/L.
Product (at use dilution	Acute Aquatic Toxicity (Calculated) LC50: 20,0000 – 90,000 mg/L.
1:100 rinse)	Acute Aquatic Toxicity NOT HAZARDOUS
Persistence and	Readily biodegradable, based on ingredients.
degradability	Readily blodegradable, based off filgredients.
Bio accumulative	No bioaccumulation is expected.
potential	
Mobility in soil	Due to its physico-chemical characteristics, highly mobile in the environment and will partition
Mobility in soil	to the aquatic compartment.
Other adverse effects	Not available
Environmental Protection	Do not discharge this material into waterways.

SECTION 13 – DISPOSAL CONSIDERATIONS		
	Dispose of waste according to applicable local and national regulations. Do not allow into drains	
	or watercourses or dispose of where ground or surface waters may be affected. Wastes	
	including emptied containers are controlled wastes and should be disposed of in accordance	
	with all applicable local and national regulations.	

SECTION 14 – TRANSPORT	INFORMATION
Labels Required	
ADG	Classified as Dangerous Goods class 3
IMDG Marine Pollutant	No



Product Name: GLISTEN WINDOW CLEANER

Date of Issue: NOV 2016 Page 6 of Total 7

HAZCHEM	●3Y
Land Transport (ADG)	
UN Number	1993
Proper Shipping Name	FLAMMABLE LIQUID, N.O.S. (ISOPROPYL ALCOHOL)
ADG Code	3
HAZCHEM Code	●3Y
Special Provisions	None allocated.
Packing Group	lli e
Packaging Method	3.8.3 RT1
Segregation	Segregation Class 3 – Flammable liquid shall not be loaded in the same vehicle or packed in the same freight container with:
	Class 1, Explosives Class 2.1, Flammable Gases, if both the Class 3 and Class 2.1 dangerous goods are in bulk Class 2.3, Toxic Gases
	Class 4.2 Spontaneously Combustible Substances
	Class 5.1 Oxidising Agents and Class 5.2, Organic Peroxides
	Class 6 Toxic Substances (where the flammable liquid is nitromethane)
	Class 7 Radioactive Substances.
	Foodstuff and foodstuff empties.

SECTION 15 – REGULATORY	INFORMATION
GHS Classification	Classified as Hazardous according to the Globally Harmonised System of Classification and
	labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.
SUSMP	Not scheduled
ADG Code	DG class 3
AICS	All ingredients present on AICS.

SECTION 16 – OTHER INFO	RMATION
Issue Date	14 th November 2016
Version Number	V 2.0
Abbreviations and	ADG Code: Australian Code for the Transport of Dangerous Goods by Road and Rail.
acronyms	AICS: Australian Inventory of Chemical Substances.
•	CAS Number: Chemical Abstracts Service Registry Number.
	GHS: Globally Harmonized System of Classification and Labelling of Chemicals
	HAZCHEM: An emergency action code of numbers and letters which gives information to emergency
	services.
	HSIS: Hazardous Substances Information System
	IARC: International Agency for Research on Cancer.
	NOHSC: National Occupational Health and Safety Commission.
	NTP: National Toxicology Program (USA).
	SDS: Safety Data Sheet
	STEL: Short Term Exposure Limit.
	SUSMP : Standard for the Uniform Scheduling of Medicines and Poisons.
	TWA: Time Weighted Average.
	UN Number: United Nations Number.
Literature references	Preparation of Safety Data Sheets for Hazardous Chemicals – Code of Practice (Safe Work Australia)
	GHS Hazardous Chemical Information List (Safe Work Australia)
	Guidance on the Classification of Hazardous Chemicals under the WHS Regulations.



Product Name: GLISTEN WINDOW CLEANER

Date of Issue: NOV 2016 Page 7 of Total 7

Disclaimer	Australian Code For The Transport Of Dangerous Goods By Road And Rail Standard for the Uniform Scheduling of Medicines and Poisons Material Safety Data Sheets – individual raw materials – Suppliers This MSDS summarizes at the date of issue our best knowledge of the health and safety hazard information of this product, and in particular how to safely handle and use this product in the workplace. Since the supplier cannot
	anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace. If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this supplier. End of SDS